

Application No. 10/772,560  
AMENDMENT  
Art Unit 3634  
Page 2

### AMENDMENTS TO THE CLAIMS

1. (Currently amended) A drag harness comprising two arm loops, each of which has a fixed length and is adapted to receive ~~one~~ a separate arm of a wearer, and a drag grip, which is joined to the arm loops solely at a common juncture and which is adapted to extend above the shoulders of the wearer and behind the head of the wearer, if the wearer is standing, whereby a rescuer grasping the drag grip can drag the wearer, via the drag harness, if the wearer is lying in a supine position.

2. (Original) The drag harness of claim 1, wherein the drag grip is a drag loop, which has a fixed length.

3. (Original) The drag harness of claim 1, which is made from strapping.

4. (Original) The drag harness of claim 2, which is made from strapping.

5. (Original) The drag harness of claim 3, which is made from a single length of strapping.

6. (Original) The drag harness of claim 4, which is made from a single length of strapping.

Application No. 10/772,560

AMENDMENT

Art Unit 3634

Page 3

7. (Original) The drag harness of claim 3, wherein the arm loops are made from a single length of strapping and wherein the drag grip is made from a separate piece of strapping.

8. (Original) The drag harness of claim 4, wherein the arm loops are made from a single length of strapping and wherein the drag loop is made from a separate piece of strapping.

9. (Original) The drag harness of claim 7, wherein the separate piece of strapping is made from flame-resistant material.

10. (Original) The drag harness of claim 8, wherein the separate piece of strapping is made from flame-resistant material.

11. (Currently amended) The drag harness of any preceding claim, wherein the drag grip, the common juncture, or both ~~are adapted to support~~ provide means for supporting the head of the wearer, when the wearer is being dragged, via the ~~head~~ drag harness, while the wearer is lying in a supine position.